

ECOLIFT WR

LOW-LEVEL ACCESS



KEY SPECIFICATIONS

Platform carrying capacity: 150 kg
Dimension: 1.28 m x 0.95 m

Working Height: 4.20 m
Total Weight: 382 kg

KEY FEATURES

- Intuitive to operate - turn handle to elevate
- Patented lift mechanism, no power required
- Lightweight, easy to manoeuvre
- Unlimited lift cycles, can be used 24/7
- Possibility to work indoor and outdoor
- Minimal operational costs, virtually maintenance free

STANDARD SPECIFICATIONS

Performance

Maximum working height	4.20 m
Maximum platform height	2.20 m
Closed platform height	0.68 m
Working outreach	0.65 m
Platform dimensions L x W	0.85 m x 0.64 m
Working foot print	1.28 m x 0.95 m
Safe Working Load	150 kg (1 person + tools)
Maximum manual force	200 N
Maximum gradient for operation	3°
Maximum wind force	Internal/external use 12.5 m/s
Maximum castor point load	171/1.68(kg/kN)
Maximum wheel force	171/1.68(kg/kN)
Power Sound Level	less than 70 dBA

Closed dimensions

Length	1.28 m
Width	0.95 m
Height	1.95 m
Weight	382 kg

STANDARD FEATURES

- Wind rated for outdoor use (12.5 m/s)
- Intuitive to operate - turn handle to elevate
- Patented lift mechanism, no power required
- Lightweight, easy to manoeuvre
- Small footprint (1.28 m x 0.95 m)
- Unlimited lift cycles, can be used 24/7
- Robust design for years of trouble free service
- Minimal operating costs, virtually maintenance free
- Auto-lok brake on elevation
- Elevates only when operated
- Interlocked lifting mechanism
- Spirit Level
- Lanyard attachment
- Emergency lowering handle
- Forklift pockets
- Fold up step
- Rubber bump pads
- Lifting points
- Durable powder coated finish
- Anti-climb basket with removable gates for emergency

ACCESSORIES & OPTIONS

- ATEX
- Steel tool tray

IMPORTANT

JLG is continually researching and developing products and reserves the right to make modifications without prior notice. All data in this document is indicative. Certain options or country standards will increase weight. Specifications may change to meet country standards or with the addition of optional equipment.

Due to continuous product improvements, JLG Industries reserves the right to make specification and/or equipment changes without prior notification.



JLG EMEA BV

Polaris Avenue 63
2132 JH Hoofddorp
The Netherlands
Tel.: +31 (0)23 565 5665
www.jlg.com

An Oshkosh Corporation Company