

# PECOLIFT

LOW-LEVEL ACCESS



## STANDARD SPECIFICATIONS

### Performance

Maximum working height	3.50 m
Maximum platform height	1.50 m
Closed platform height	0.3 m
Platform dimensions L x W	0.72 m x 0.6 m
Working footprint	0.99 m x 0.70 m
Safe working load	150 kg (1 person + tools)
Maximum manual force	200 N
Maximum gradient for operation	0,5 °
Maximum wind force	Internal use only 0 m/s
Maximum castor point load	125 kg / 1.23 kN
Maximum wheel force	125 kg / 1.23 kN
Power Sound Level	less than 70 dBA

### Closed dimensions

Length	0.99 m
Width	0.70 m
Height	1.55 m
Weight	196 kg

## KEY SPECIFICATIONS

**Platform carrying capacity:**  
150 kg

**Dimension:**  
0.99 m x 0.70 m

**Working Height:**  
3.50 m

**Total Weight:**  
196 kg

## KEY FEATURES

- Intuitive to operate - turn handle to elevate
- Patented lift mechanism, no power required
- Lightweight, easy to manoeuvre
- Small footprint (0.99 m x 0.70 m)
- Unlimited lift cycles, can be used 24/7
- Robust design for years of trouble-free service
- Minimal operational costs, virtually maintenance free

## STANDARD FEATURES

- Intuitive to operate – turn handle to elevate
- Patented lift mechanism, no power required
- Lightweight, easy to manoeuvre
- Small footprint (0.99 m x 0.70 m)
- Unlimited lift cycles, can be used 24/7
- Robust design for years of trouble free service
- Minimal operating costs, virtually maintenance free
- Auto-lok brake on elevation
- Auto-braked on entering basket
- Elevates only when operated
- Interlocked lifting mechanism
- Spirit Level
- Lanyard attachment
- Emergency lowering handle
- Forklift pockets
- Durable powder coated finish
- Anti-climb basket with removable gates for emergency

## ACCESSORIES & OPTIONS

- ATEX
- Tool Tethering options
- Tool tray
- Transport Wheels

### IMPORTANT

JLG is continually researching and developing products and reserves the right to make modifications without prior notice. All data in this document is indicative. Certain options or country standards will increase weight. Specifications may change to meet country standards or with the addition of optional equipment.

Due to continuous product improvements, JLG Industries reserves the right to make specification and/or equipment changes without prior notification.



### JLG EMEA BV

Polaris Avenue 63  
2132 JH Hoofddorp  
The Netherlands  
Tel.: +31 (0)23 565 5665  
[www.jlg.com](http://www.jlg.com)

An Oshkosh Corporation Company